

PERFORMANCE LEVEL

		STAR75	STAR75 VV	STAR75 LUXUS
UW-VALUE		0.94 W/m²K*	0.95 W/m²K	1.1 W/m ² K
UF-VALUE	1.5 (RS) - 1.2 (RSi) - 0.97 W/m²K (RSi+/Hi)		1.1 W/m²K	0.97 W/m²K
AIR TRANSMISSION	NBN EN 12207	Klasse 4	Klasse 4	Klasse 4
WATERTIGHTNESS	NBN EN 12208	Klasse E1200A	Klasse E1350A	Klasse E1200A
RESISTANCE TO WIND	NBN EN 12210	Klasse C5	Klasse C5	Klasse C5
SHOCK RESISTANCE	NBN EN 13049	Klasse 4	Klasse 5	Klasse 4
BURGLARPROOF	NEN 5096 / ENV 1627	RC2 - RC3 (flat door)	-	RC2 - RC3 (flat door)
OPERATING FORCE	EN 13115	Klasse 1	Klasse 1	Klasse 1
ACOUSTICAL INSULATION		tot 47.1dB (-1; -4)	tot 46dB (-1.9; -6.1)	tot 47.1dB (-1; -4)
FIRE RESISTANT		EW30 - EI30	EW30 - El30	EW30 - EI30

^{* 1230}mm x 1480mm; UG: 0.6W/m²K & PSI: 0.036W/MK - profile combination: RS010-RS020(RSi+)

APPLICATIONS

- Fixed frames
- Pivoting windows:
- Single or double hinged with the option of tilting
- Possible pivot direction: inside opening
- Flat and rebate doors both single and double opening, inward en outward opening (RS + RX LUX)
- Inward opening windowdoor with threshold (RS VV)
- Wing-covered panel doors

25-YEAR COLOUR GUARANTEE



Aliplast gives a 25-year guarantee on 50 current colours. The Qualicoat Seaside quality label ensures that your paint colour is extra protected against

aggressive environments (exhaust fumes, salty sea air, etc.). You enjoy a 15-year guarantee on all other colours. Peace of mind for the future.

100% MADE IN BELGIUM



tailored to current housing needs.

coating, insulation and transport to the Aliplast distributors. The distributors produce and install the finished windows in your building project.

DURABLE PRODUCT



therefore be completely reused without

compromising on quality. Aliplast was awarded the Cradle to Cradle certificate on this system: it is suitable for circular







STAR75

united in one window system.

The latest technologies and innovations

Aliplast develops aluminium profiles Everything happens under one roof: from drawing to extrusion, powder


Aluminium is a durable product because it has a long lifespan. Moreover, the material is fully recyclable and can

construction, it has a positive impact on people and the environment, it contains no harmful substances and is manufactured using green energy.

STAR75

STYLE AND INSULATION VARIANTS







STAR75 i

















STAR75 i+

STAR75 HI



INVISIBLE





STAR75 LUXUS







STAR75: FOR EVERY ARCHITECTURAL STYLE

The latest technologies and innovations united in one window system. The clean design of the Star75 combined with its ultra-performance insulation makes it an ideal window system for low-energy houses, both in new builds and renovations. Curved windows? That is also possible. Aliplast bends the aluminium profiles in its own workshop. Choose from 3 styles: Modern, Invisible - Hidden Sash or Luxus.

	STAR75 / i / i+ / Hi	STAR75 INVISIBLE /VV	STAR75 LUXUS
Minimal sight line inward opening window	Outer frame: 55 mm Sash: 45 mm	Outer frame + Sash: 76 mm	Outer frame: 65 mm Sash: 45 mm
Minimal sight line inward opening flat door	Outer frame: 70 mm Sash: 72 mm	nvt	nvt
Minimal sight line outward opening flat door	Outer frame: 50 mm Sash: 92 mm	nvt	nvt
Minimal sight line T-profile	77 mm	136 mm	77 mm
Built-in depth outer frame	75 mm	75 mm	90 mm
Built-in depth sash	84 mm	84 mm	94 mm
lazing rebate 22 of 25 mm		15 mm	22 mm
Glazing	Outer frame: 12 mm - 60 mm Sash: 21 mm - 69 mm	Outer frame: 12 mm - 60 mm Sash: 26 mm - 58 mm	Outer frame: 12 mm - 60 mm Sash: 21 mm - 69 mm
Thermal insulation	Highly insulating Noryl strips (A	ATG/H726) for all styles + Noryl strips w	ith aluminium foil for the Hi vers